

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Professional warranty (in years)</b>	-	5 years limited
<b>Pattern</b>	-	Veneto
<b>Pattern type</b>	-	Allover
<b>Laying direction</b>	-	Same Direction
<b>Format Type</b>	-	Roll
<b>ASTM Product type</b>	-	Sheet Linoleum Floor Covering (ASTM F2034)
<b>Surface treatment</b>	-	xf <sup>2</sup>
<b>Total thickness</b>	ASTM F386	0.100 " (2.50 mm)
<b>Flexibility</b>	ISO 24344 Method A	≤ 30 mm ø
<b>Installation method</b>	-	Glue-Down
<b>Residual indentation ASTM F1914</b>	-	6 mil (0.15 mm)

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>ReStart® Ready</b>	-	Yes
<b>Rapidly renewable content</b>	-	75 %
<b>Cradle-to-Cradle</b>	-	Silver
<b>Phthalate content</b>	-	Phthalate-free
<b>Floorscore certification</b>	-	Yes
<b>Pre Consumer recycled content</b>	-	34 %
<b>NSF 332 Certification</b>	-	Platinum