

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Professional warranty (in years)</b>	-	5 years limited
<b>Pattern</b>	-	Metallurgy
<b>Pattern type</b>	-	Allover
<b>Format Type</b>	-	Tile
<b>ASTM Product type</b>	-	Rubber Floor Tile (ASTM F1344)
<b>Total thickness</b>	ASTM F386	0.125 " (3.20 mm)
<b>Installation method</b>	-	Glue-Down
<b>Flooring Radiant Panel</b>	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
<b>Smoke Generation</b>	ASTM E662	< 450
<b>Static Load Limit</b>	ASTM F970	Pass
<b>Chemical Resistance</b>	ASTM F925	Good
<b>Heat stability</b>	ASTM F1514	$\Delta E \leq 8.0$
<b>Slip resistance</b>	ASTM D2047	SCOF $\geq 0.8$

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>ReStart®</b>	-	Yes
<b>Cradle-to-Cradle</b>	-	Bronze
<b>Floorscore certification</b>	-	Yes