

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Pattern	-	Cable Weave 60127
Pattern type	-	Texture
Format Type	-	Roll
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Total thickness	-	0.380 " (9.65 mm)
Installation method	-	Glue-Down
Commercial warranty	-	15 year limited
Flammability - Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	0.8 kV
Colorfastness to Light	AATCC 16E	> 4 after 100 hours
Smoke Generation	ASTM E662	< 450
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	6.820 "
Pattern repeat width	-	16 "
Construction	-	Woven Patterned Loop
Dye Method	-	Solution Dyed
Fiber System	-	Dynex SD® Nylon
Secondary backing	-	Crossweave®
Stitches/Rows per Inch	-	8.80 /in
Pile thickness	ASTM D5848	0.245 " (6.17 mm)
Average pile height	-	0.215 " (6 mm)
Type of product	-	Textile Flooring

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP1828
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product