

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
Construction Process	ISO 2424	WOVEN
Total thickness	-	0.380 " (9.65 mm)
Installation method	-	Glue-Down
Format Type	-	Roll
Commercial warranty	-	15 year limited
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	Crossweave®
Pile construction	-	Patterned loop pile
Pile thickness	ISO 1766	0.245 " (6.17 mm)
Face Weight	-	36 oz/yd <sup>2</sup>
Pile density	ISO 8543	5326 oz/yd <sup>3</sup>
Dye Method	-	Solution dyed
Fiber System	ISO 2424	Dynex SD® Nylon

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Electrostatic Propensity	-	$\leq 3.5$ kV
Is cuttable	-	Yes
Total thickness	-	0.380 " (9.65 mm)
Installation method	-	Glue-Down
Format Type	-	Roll

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP100204
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Recycled Content - Production Waste	-	0 %
Post Consumer recycled content	-	0 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	-	Woven Patterned Loop
Maximum pile height	-	0.2950 " (7.49 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned loop pile

	Standard	Tarkett value
<b>Surface Flammability</b>	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
<b>Total thickness</b>	ASTM F386	0.380 " (9.65 mm)
<b>Electrostatic Propensity</b>	-	≤ 3.5 kV
<b>Stitches/Rows per Inch</b>	-	8.80 /in
<b>Pile thickness</b>	ASTM D5848	0.245 " (6.17 mm)
<b>Average pile height</b>	-	0.215 " (6 mm)
<b>Minimum pile height</b>	-	0.1380 " (3.51 mm)
<b>Pile density</b>	-	5326 oz/yd <sup>3</sup>
<b>Fiber System</b>	-	Dynex SD® Nylon
<b>Dye Method</b>	-	Solution dyed
<b>Secondary backing</b>	-	Crossweave®
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Cable Weave 60127
<b>Pattern type</b>	-	Texture
<b>Pattern scale</b>	-	Small
<b>Pattern match</b>	-	Yes
<b>Pattern repeat length</b>	-	173.23 "
<b>Pattern repeat width</b>	-	406.40 "
<b>Format Type</b>	-	Roll
<b>Commercial warranty</b>	-	15 year limited
<b>Flammability</b>	ASTM E648	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
<b>Smoke Density</b>	ASTM E662	< 450
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Type of product</b>	-	Textile Flooring
<b>Length</b>	-	1800 "
<b>Width</b>	-	144 "