

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

## SUSTAINABILITY, ENVIRONMENT &amp; INDOOR AIR QUALITY

	Standard	Tarkett value
<b>CRI Green Label Plus Certification</b>	-	GLP100204
<b>ReStart®</b>	-	Yes
<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product
<b>Recycled Content - Production Waste</b>	-	0 %
<b>Post Consumer recycled content</b>	-	0 %

## CHARACTERISTICS &amp; TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Construction</b>	-	Woven Textured Loop
<b>Soil protection</b>	-	Application Rate: 2% of Face Weight
<b>Maximum pile height</b>	-	0.2370 " (6.02 mm)
<b>Pile construction</b>	-	Textured loop pile
<b>Surface Flammability</b>	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
<b>Electrostatic Propensity</b>	-	≤ 3.5 kV
<b>Stitches/Rows per Inch</b>	-	8.60 /in
<b>Pile thickness</b>	ASTM D5848	0.220 " (5.61 mm)
<b>Average pile height</b>	-	0.160 " (4 mm)
<b>Minimum pile height</b>	-	0.0790 " (2.01 mm)
<b>Pile density</b>	-	6517 oz/yd <sup>3</sup>
<b>Fiber System</b>	-	Dynex SD® Nylon
<b>Dye Method</b>	-	Solution dyed
<b>Secondary backing</b>	-	Crossweave®
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Full Volume III 60102
<b>Pattern type</b>	-	Texture
<b>Pattern scale</b>	-	Medium
<b>Pattern match</b>	-	Yes
<b>Pattern repeat length</b>	-	0.45 "
<b>Pattern repeat width</b>	-	0.40 "
<b>Format Type</b>	-	Roll
<b>Commercial warranty</b>	-	15 year limited
<b>Flammability</b>	ASTM E648	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
<b>Smoke Density</b>	ASTM E662	< 450