

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Maximum pile height	-	0.2370 " (6.02 mm)
Construction	-	Woven Loop
Pile construction	-	Textured loop pile
Stitches/Rows per Inch	-	8.80 /in
Pile thickness	ASTM D5848	0.195 " (4.95 mm)
Average pile height	-	0.175 " (4 mm)
Minimum pile height	-	0.1170 " (2.97 mm)
Pile density	-	5465 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	Crossweave®
Installation method	-	Glue-Down
Pattern type	-	Texture
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	0.45 "
Pattern repeat width	-	0.40 "
Format Type	-	Roll
Soil protection	-	Application Rate: 2% of Face Weight
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Commercial warranty	-	15 year limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP100204
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %