

**TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS**

**CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS**

	Standard	Tarkett value
<b>Flooring Radiant Panel</b>	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
<b>Smoke Generation</b>	ASTM E662	< 450
<b>Pattern</b>	-	Plaited STI 60131
<b>Pattern type</b>	-	Linear
<b>Pattern scale</b>	-	Small
<b>Pattern repeat length</b>	-	2.170 "
<b>Pattern repeat width</b>	-	0.400 "
<b>Format Type</b>	-	Roll
<b>Dye Method</b>	-	Solution Dyed / Space Dyed
<b>Fiber System</b>	-	Dynex® Nylon
<b>Face Weight</b>	-	40 oz/yd <sup>2</sup>
<b>Installation method</b>	-	Glue-Down
<b>Professional warranty (in years)</b>	-	15 year limited

**SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY**

	Standard	Tarkett value
<b>ReStart®</b>	-	Yes
<b>CRI Green Label Plus Certification</b>	-	GLP1828