

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

|                             | Standard | Tarkett value                             |
|-----------------------------|----------|---|
| <b>Pile thickness</b>       | ISO 1766 | 0.230 " (5.79 mm)                         |
| <b>Fiber System</b>         | ISO 2424 | Dynex® Nylon                              |
| <b>Format Type</b>          | -        | Roll                                      |
| <b>Construction Process</b> | ISO 2424 | WOVEN                                     |
| <b>Installation method</b>  | -        | Glue-Down                                 |
| <b>Commercial warranty</b>  | -        | 15 year limited                           |
| <b>Surface treatment</b>    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>    | ISO 2424 | Crossweave®                               |
| <b>Pile construction</b>    | -        | Textured loop pile                        |
| <b>Face Weight</b>          | -        | 40 oz/yd <sup>2</sup>                     |
| <b>Pile density</b>         | ISO 8543 | 5355 oz/yd <sup>3</sup>                   |
| <b>Dye Method</b>           | -        | Solution Dyed / Space Dyed                |

### TECHNICAL PERFORMANCE

|                                 | Standard | Tarkett value                             |
|---------------------------------|----------|---|
| <b>Flammability</b>             | -        | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Electrostatic Propensity</b> | -        | $\leq 3.5$ kV                             |
| <b>Colorfastness to Light</b>   | -        | $\geq 4$ after 60 hours                   |
| <b>Is cutable</b>               | -        | Yes                                       |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|  | Standard | Tarkett value  |
|--|----------|--|
| <b>ReStart®</b>                            | -        | Yes  |
| <b>CRI Green Label Plus Certification</b>  | -        | GLP100204  |
| <b>Recycled Content - Production Waste</b> | -        | 0 %  |
| <b>Antimicrobial Chemicals</b>             | -        | No antimicrobials (EPA Registered pesticides) added to product |
| <b>Post Consumer recycled content</b>      | -        | 0 %  |

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                            | Standard  | Tarkett value                             |
|----------------------------|-----------|---|
| <b>Type of product</b>     | -         | Textile Flooring                          |
| <b>Length</b>              | -         | 1800 "                                    |
| <b>Width</b>               | -         | 144 "                                     |
| <b>Pattern</b>             | -         | Plaited STI 60131                         |
| <b>Commercial warranty</b> | -         | 15 year limited                           |
| <b>Flammability</b>        | ASTM E648 | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Smoke Density</b>       | ASTM E662 | < 450                                     |

|                                 | Standard   | Tarkett value                             |
|---------------------------------|------------|---|
| <b>Surface treatment</b>        | -          | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>      | -          | Glue-Down                                 |
| <b>Pattern type</b>             | -          | Linear                                    |
| <b>Format Type</b>              | -          | Roll                                      |
| <b>Construction</b>             | -          | Woven Textured Loop                       |
| <b>Soil protection</b>          | -          | Application Rate: 2% of Face Weight       |
| <b>Maximum pile height</b>      | -          | 0.2770 " (7.04 mm)                        |
| <b>Pile construction</b>        | -          | Textured loop pile                        |
| <b>Surface Flammability</b>     | -          | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| <b>Electrostatic Propensity</b> | -          | ≤ 3.5 kV                                  |
| <b>Colorfastness to Light</b>   | AATCC 16E  | ≥ 4 after 60 hours                        |
| <b>Stitches/Rows per Inch</b>   | -          | 9.20 /in                                  |
| <b>Pile thickness</b>           | ASTM D5848 | 0.230 " (5.79 mm)                         |
| <b>Average pile height</b>      | -          | 0.195 " (5 mm)                            |
| <b>Minimum pile height</b>      | -          | 0.1170 " (2.97 mm)                        |
| <b>Pile density</b>             | -          | 5355 oz/yd <sup>2</sup>                   |
| <b>Fiber System</b>             | -          | Dynex® Nylon                              |
| <b>Dye Method</b>               | -          | Solution Dyed / Space Dyed                |
| <b>Secondary backing</b>        | -          | Crossweave®                               |
| <b>Pattern scale</b>            | -          | Small                                     |
| <b>Pattern match</b>            | -          | Yes                                       |
| <b>Pattern repeat length</b>    | -          | 2.17 "                                    |
| <b>Pattern repeat width</b>     | -          | 0.40 "                                    |