

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450
Pattern	-	Plaited STI 60131
Pattern type	-	Linear
Pattern scale	-	Small
Pattern repeat length	-	2.170 " , 0.660 "
Pattern repeat width	-	0.400 "
Format Type	-	Roll
Dye Method	-	Solution Dyed / Space Dyed, Solution Dyed
Fiber System	-	Dynex® Nylon, Dynex SD® Nylon
Secondary backing	-	Crossweave®, CrossCushion®
Total thickness	ASTM F386	0.420 " (10.67 mm), 0.410 " (10.41 mm), 0.520 " (13.21 mm)
Face Weight	-	40 oz/yd ² , 36 oz/yd ²
Installation method	-	Glue-Down
Professional warranty (in years)	-	15 year limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP1828
Post Consumer recycled content	-	8 %