

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	ISO 2424	WOVEN
Total thickness	-	0.380 " (9.65 mm)
Installation method	-	Glue-Down
Format Type	-	Roll
Commercial warranty	-	15 year limited
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	Crossweave®
Pile construction	-	Textured cut and loop pile
Pile thickness	ISO 1766	0.220 " (5.59 mm)
Face Weight	-	42 oz/yd ²
Pile density	ISO 8543	6835 oz/yd ³
Dye Method	-	Solution Dyed / Space Dyed
Fiber System	ISO 2424	Dynex® Nylon

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 (≥ 0.45 W/cm ²)
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	-	≥ 4 after 60 hours
Is cuttable	-	Yes

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP100204
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Recycled Content - Production Waste	-	0 %
Post Consumer recycled content	-	0 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	-	Woven Textured Cut & Loop
Maximum pile height	-	0.2200 " (5.59 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Textured cut and loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.380 " (9.65 mm)

	Standard	Tarkett value
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	AATCC 16E	≥ 4 after 60 hours
Stitches/Rows per Inch	-	9.60 /in
Pile thickness	ASTM D5848	0.220 " (5.59 mm)
Average pile height	-	0.220 " (6 mm)
Pile density	-	6835 oz/yd ³
Fiber System	-	Dynex® Nylon
Dye Method	-	Solution Dyed / Space Dyed
Secondary backing	-	Crossweave®
Installation method	-	Glue-Down
Pattern	-	Reprise 60128
Pattern type	-	Texture
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	0.42 "
Pattern repeat width	-	0.40 "
Format Type	-	Roll
Commercial warranty	-	15 year limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Type of product	-	Textile Flooring
Length	-	1800 "
Width	-	144 "