

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CLASSIFICATION

|                            | Standard  | Tarkett value                             |
|----------------------------|-----------|---|
| <b>Surface treatment</b>   | -         | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Pattern</b>             | -         | Alhambra 40043                            |
| <b>Pattern type</b>        | -         | Geometric                                 |
| <b>Format Type</b>         | -         | Roll                                      |
| <b>Commercial warranty</b> | -         | 20 year limited                           |
| <b>Flammability</b>        | ASTM E648 | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Smoke Density</b>       | ASTM E662 | < 450                                     |

### CHARACTERISTICS

|                             | Standard | Tarkett value                             |
|-----------------------------|----------|---|
| <b>Pile thickness</b>       | ISO 1766 | 0.080 " (2.01 mm)                         |
| <b>Fiber System</b>         | ISO 2424 | Dynex SD® Nylon                           |
| <b>Format Type</b>          | -        | Roll                                      |
| <b>Construction Process</b> | ISO 2424 | TUFTED                                    |
| <b>Installation method</b>  | -        | Glue-Down                                 |
| <b>Commercial warranty</b>  | -        | 20 year limited                           |
| <b>Surface treatment</b>    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>    | ISO 2424 | LifeLONG®                                 |
| <b>Pile construction</b>    | -        | Patterned Tipshear                        |
| <b>Gauge</b>                | -        | 5/64"                                     |
| <b>Face Weight</b>          | -        | 36 oz/yd <sup>2</sup>                     |
| <b>Pile density</b>         | ISO 8543 | 9098 oz/yd <sup>3</sup>                   |
| <b>Dye Method</b>           | -        | Solution dyed                             |
| <b>Primary backing</b>      | -        | Woven Polypropylene                       |

### TECHNICAL PERFORMANCE

|                                 | Standard | Tarkett value                             |
|---------------------------------|----------|---|
| <b>Flammability</b>             | -        | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Electrostatic Propensity</b> | -        | $\leq 3.5$ kV                             |
| <b>Colorfastness to Light</b>   | -        | $\geq 4$ after 100 hours                  |
| <b>Is cuttable</b>              | -        | Yes                                       |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|  | Standard | Tarkett value |
|--|----------|---------------|
| <b>ReStart®</b>                            | -        | Yes           |
| <b>CRI Green Label Plus Certification</b>  | -        | GLP100160     |
| <b>Recycled Content - Production Waste</b> | -        | 28 %          |

|                                | Standard | Tarkett value  |
|--------------------------------|----------|--|
| Antimicrobial Chemicals        | -        | No antimicrobials (EPA Registered pesticides) added to product |
| Post Consumer recycled content | -        | 0 %  |

## CHARACTERISTICS & TECHNICAL PERFORMANCE

|                          | Standard     | Tarkett value                             |
|--------------------------|--------------|---|
| Type of product          | -            | Textile Flooring                          |
| Length                   | -            | 1800 "                                    |
| Width                    | -            | 150 "                                     |
| Pattern                  | -            | Alhambra 40043                            |
| Commercial warranty      | -            | 20 year limited                           |
| Flammability             | ASTM E648    | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| Smoke Density            | ASTM E662    | < 450                                     |
| Surface treatment        | -            | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method      | -            | Glue-Down                                 |
| Pattern type             | -            | Geometric                                 |
| Format Type              | -            | Roll                                      |
| Soil protection          | -            | Application Rate: 2% of Face Weight       |
| Maximum pile height      | -            | 0.1970 " (5 mm)                           |
| Stain Resistance         | AATCC 175-08 | $\geq 8$                                  |
| Pile construction        | -            | Patterned Tipshear                        |
| Surface Flammability     | -            | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| Electrostatic Propensity | -            | $\leq 3.5$ kV                             |
| Gauge                    | -            | 5/64"                                     |
| Colorfastness to Light   | AATCC 16E    | $\geq 4$ after 100 hours                  |
| Stitches/Rows per Inch   | -            | 11.60 /in                                 |
| Pile thickness           | ASTM D5848   | 0.080 " (2.01 mm)                         |
| Minimum pile height      | -            | 0.0790 " (2.01 mm)                        |
| Pile density             | -            | 9098 oz/yd <sup>3</sup>                   |
| Fiber System             | -            | Dynex SD® Nylon                           |
| Dye Method               | -            | Solution dyed                             |
| Secondary backing        | -            | LifeLONG®                                 |
| Primary backing          | -            | Woven Polypropylene                       |
| Pattern scale            | -            | Large                                     |
| Pattern match            | -            | Yes                                       |
| Pattern repeat length    | -            | 8.62 "                                    |
| Pattern repeat width     | -            | 18.75 "                                   |