

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Pattern	-	Alhambra 40043
Pattern type	-	Geometric
Format Type	-	Roll
Surface treatment	-	Ensure
Total thickness	-	0.205 " (5.26 mm)
Installation method	-	Glue-Down
Commercial warranty	-	20 years
Flammability - Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Colorfastness to Light	AATCC 16E	> 4 after 100 hours
Smoke Generation	ASTM E662	< 450
Pattern match	-	Yes
Pattern repeat length	-	8.620 "
Pattern repeat width	-	18.750 "
Dye Method	-	Solution Dyed
Primary backing	-	Woven Polypropylene
Secondary backing	-	LifeLONG®
Type of product	-	Textile Flooring

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	32 %
CRI Green Label Plus Certification	-	GLP6595
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product