

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	EN 13329	0.265 " (6.73 mm)
Installation method	-	Glue-Down
Format Type	-	Roll
Commercial warranty	-	10 year limited
Gauge	-	5/64"
Face Weight	-	33 oz/yd ²
Primary backing	-	Woven Polypropylene

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP0025
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Maximum pile height	-	0.1790 " (4.55 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.265 " (6.73 mm)
Electrostatic Propensity	-	≤ 3.5 kV
Gauge	-	5/64"
Colorfastness to Light	AATCC 16E	≥ 4 after 60 hours
Stitches/Rows per Inch	-	12 /in
Minimum pile height	-	0.0790 " (2.01 mm)
Pile density	-	6871 oz/yd ³
Fiber System	-	Dynex® Nylon
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Installation method	-	Glue-Down
Pattern	-	Breakout 40035
Pattern type	-	Geometric
Pattern scale	-	Large

	Standard	Tarkett value
Pattern match	-	Yes
Pattern repeat length	-	33.33 "
Pattern repeat width	-	18.75 "
Format Type	-	Roll
Commercial warranty	-	10 year limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Length	-	150 ft (46 m)
Type of product	-	Textile Flooring
Width	-	12.5 ft (3.81 m)