

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450
Pattern	-	Broccato 40030
Pattern type	-	Organic
Pattern scale	-	Large
Pattern repeat length	-	30.910 "
Pattern repeat width	-	18.750 "
Format Type	-	Roll
Dye Method	-	Solution Dyed
Fiber System	-	Dynex SD® Nylon
Primary backing	-	Woven Polypropylene
Secondary backing	-	LifeLONG®, Super-Lok®, ErgoStep®
Total thickness	ASTM F386	0.246 " (6.25 mm), 0.346 " (8.79 mm)
Face Weight	-	32 oz/yd ²
Installation method	-	Glue-Down
Professional warranty (in years)	-	20 years, 10 years, 10 year limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP6595, GLP1828
Pre Consumer recycled content	-	34 %, 0 %
Post Consumer recycled content	-	10 %