

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Commercial warranty	-	10 year limited
Total thickness	ASTM F386	0.225 " (5.77 mm)
Installation method	-	Glue-Down
Pattern	-	Grama II 44025
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Texture
Format Type	-	Roll
Maximum pile height	-	0.1770 " (4.50 mm)
Pile construction	-	Patterned loop pile
Gauge	-	1/10"
Stitches/Rows per Inch	-	12 /in
Minimum pile height	-	0.0980 " (2.49 mm)
Pile density	-	6326 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	0.30 "
Pattern repeat width	-	0.20 "
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	≥ 8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	AATCC 16E	≥ 4 after 100 hours
Face Weight	-	22 oz/yd ²

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP1828
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product