

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	ISO 24346	0.225 " (5.77 mm)
Installation method	-	Glue-Down
Format Type	-	Roll
Commercial warranty	-	10 year limited
Pile construction	-	Textured loop pile
Gauge	-	1/10"
Face Weight	-	22 oz/yd ²
Pile density	ISO 8543	6036 oz/yd ³
Dye Method	-	Solution Dyed
Secondary backing	ISO 2424	Super-Lok®
Primary backing	-	Woven Polypropylene
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 (≥ 0.45 W/cm ²)
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	-	≥ 4 after 100 hours

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP0025
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Maximum pile height	-	0.1770 " (4.50 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Textured loop pile
Stain Resistance	AATCC 175-08	≥ 8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.225 " (5.77 mm)
Electrostatic Propensity	-	≤ 3.5 kV

	Standard	Tarkett value
Gauge	-	1/10"
Colorfastness to Light	AATCC 16E	≥ 4 after 100 hours
Stitches/Rows per Inch	-	12 /in
Minimum pile height	-	0.0980 " (2.49 mm)
Pile density	-	6036 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Installation method	-	Glue-Down
Pattern	-	Grama Striae II 44040
Pattern type	-	Linear
Pattern scale	-	Medium
Pattern match	-	Yes
Pattern repeat length	-	0.30 "
Pattern repeat width	-	28.80 "
Format Type	-	Roll
Commercial warranty	-	10 year limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Type of product	-	Textile Flooring
Length	-	150 ft (46 m)
Width	-	12 ft (3.66 m)