

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

|                             | Standard | Tarkett value                             |
|-----------------------------|----------|---|
| <b>Pile thickness</b>       | ISO 1766 | 0.255 " (6.50 mm)                         |
| <b>Fiber System</b>         | ISO 2424 | Dynex SD® Nylon                           |
| <b>Format Type</b>          | -        | Roll                                      |
| <b>Construction Process</b> | ISO 2424 | TUFTED                                    |
| <b>Installation method</b>  | -        | Glue-Down                                 |
| <b>Commercial warranty</b>  | -        | 10 year limited                           |
| <b>Surface treatment</b>    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>    | ISO 2424 | Super-Lok®                                |
| <b>Pile construction</b>    | -        | Patterned Tipshear                        |
| <b>Gauge</b>                | -        | 1/10"                                     |
| <b>Face Weight</b>          | -        | 23 oz/yd <sup>2</sup>                     |
| <b>Pile density</b>         | ISO 8543 | 5671 oz/yd <sup>3</sup>                   |
| <b>Dye Method</b>           | -        | Solution dyed                             |
| <b>Primary backing</b>      | -        | Woven Polypropylene                       |

### TECHNICAL PERFORMANCE

|                                 | Standard | Tarkett value                             |
|---------------------------------|----------|---|
| <b>Flammability</b>             | -        | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Electrostatic Propensity</b> | -        | $\leq 3.5$ kV                             |
| <b>Colorfastness to Light</b>   | -        | $\geq 4$ after 100 hours                  |
| <b>Is cuttable</b>              | -        | Yes                                       |
| <b>Surface treatment</b>        | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>      | -        | Glue-Down                                 |
| <b>Format Type</b>              | -        | Roll                                      |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|  | Standard | Tarkett value  |
|--|----------|--|
| <b>ReStart®</b>                            | -        | Yes  |
| <b>CRI Green Label Plus Certification</b>  | -        | GLP0025  |
| <b>Recycled Content - Production Waste</b> | -        | 0 %  |
| <b>Antimicrobial Chemicals</b>             | -        | No antimicrobials (EPA Registered pesticides) added to product |
| <b>Post Consumer recycled content</b>      | -        | 0 %  |

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                        | Standard | Tarkett value    |
|------------------------|----------|------------------|
| <b>Type of product</b> | -        | Textile Flooring |
| <b>Length</b>          | -        | 1800 "           |

|                                 | Standard     | Tarkett value                             |
|---------------------------------|--------------|---|
| <b>Width</b>                    | -            | 144 "                                     |
| <b>Pattern</b>                  | -            | Loci III 44030                            |
| <b>Commercial warranty</b>      | -            | 10 year limited                           |
| <b>Flammability</b>             | ASTM E648    | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Smoke Density</b>            | ASTM E662    | < 450                                     |
| <b>Surface treatment</b>        | -            | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>      | -            | Glue-Down                                 |
| <b>Pattern type</b>             | -            | Texture                                   |
| <b>Format Type</b>              | -            | Roll                                      |
| <b>Soil protection</b>          | -            | Application Rate: 2% of Face Weight       |
| <b>Maximum pile height</b>      | -            | 0.1770 " (4.50 mm)                        |
| <b>Stain Resistance</b>         | AATCC 175-08 | $\geq 8$                                  |
| <b>Pile construction</b>        | -            | Patterned Tipshear                        |
| <b>Surface Flammability</b>     | -            | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| <b>Electrostatic Propensity</b> | -            | $\leq 3.5$ kV                             |
| <b>Gauge</b>                    | -            | 1/10"                                     |
| <b>Colorfastness to Light</b>   | AATCC 16E    | $\geq 4$ after 100 hours                  |
| <b>Stitches/Rows per Inch</b>   | -            | 8.10 /in                                  |
| <b>Pile thickness</b>           | ASTM D5848   | 0.255 " (6.50 mm)                         |
| <b>Minimum pile height</b>      | -            | 0.0970 " (2.46 mm)                        |
| <b>Pile density</b>             | -            | 5671 oz/yd <sup>3</sup>                   |
| <b>Fiber System</b>             | -            | Dynex SD® Nylon                           |
| <b>Dye Method</b>               | -            | Solution dyed                             |
| <b>Secondary backing</b>        | -            | Super-Lok®                                |
| <b>Primary backing</b>          | -            | Woven Polypropylene                       |
| <b>Pattern scale</b>            | -            | Small                                     |
| <b>Pattern match</b>            | -            | Yes                                       |
| <b>Pattern repeat length</b>    | -            | 7.90 "                                    |
| <b>Pattern repeat width</b>     | -            | 0.40 "                                    |