

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Smoke Generation</b>	ASTM E662	< 450
<b>Pattern</b>	-	Okame 40015
<b>Pattern type</b>	-	Organic
<b>Pattern scale</b>	-	Large
<b>Pattern repeat length</b>	-	42.120 "
<b>Pattern repeat width</b>	-	18.750 "
<b>Format Type</b>	-	Roll
<b>Dye Method</b>	-	Solution Dyed / Space Dyed
<b>Fiber System</b>	-	TDX® Nylon
<b>Secondary backing</b>	-	ErgoStep®
<b>Total thickness</b>	ASTM F386	0.405 " (10.29 mm)
<b>Face Weight</b>	-	37 oz/yd <sup>2</sup>
<b>Installation method</b>	-	Glue-Down
<b>Professional warranty (in years)</b>	-	10 year limited

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>Pre Consumer recycled content</b>	-	0 %
<b>Post Consumer recycled content</b>	-	0 %