

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Maximum pile height	-	0.2370 " (6.02 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned Tipshear
Stain Resistance	AATCC 175-08	≥8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.305 " (7.75 mm)
Electrostatic Propensity	-	≤ 3.5 kV
Gauge	-	1/10"
Colorfastness to Light	AATCC 16E	≥ 4 after 100 hours
Stitches/Rows per Inch	-	13 /in
Minimum pile height	-	0.0790 " (2.01 mm)
Pile density	-	7643 oz/yd <sup>3</sup>
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution dyed
Secondary backing	-	LifeLONG®
Primary backing	-	Woven Polypropylene
Installation method	-	Glue-Down
Pattern	-	Plumeria 44060
Pattern type	-	Organic
Pattern scale	-	Large
Pattern match	-	Yes
Pattern repeat length	-	1016 "
Pattern repeat width	-	609.60 "
Format Type	-	Roll
Commercial warranty	-	20 year limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
Smoke Density	ASTM E662	< 450

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP100160
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Recycled Content - Production Waste	-	28 %
Post Consumer recycled content	-	0 %