

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	EN 13329	0.385 " (9.75 mm)
Installation method	-	Glue-Down
Format Type	-	Roll
Commercial warranty	-	10 year limited
Gauge	-	1/10"
Face Weight	-	46 oz/yd ²
Primary backing	-	Woven Polypropylene

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP0025
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Maximum pile height	-	0.2750 " (6.99 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Tip-sheared pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.385 " (9.75 mm)
Electrostatic Propensity	-	≤ 3.5 kV
Gauge	-	1/10"
Colorfastness to Light	AATCC 16E	≥ 4 after 60 hours
Stitches/Rows per Inch	-	10.20 /in
Minimum pile height	-	0.2570 " (6.53 mm)
Pile density	-	5571 oz/yd ³
Fiber System	-	Antron® Legacy Nylon
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Installation method	-	Glue-Down
Pattern	-	Suri 44043
Pattern type	-	Texture
Pattern scale	-	Small

	Standard	Tarkett value
Pattern match	-	No
Pattern repeat width	-	0.20 "
Format Type	-	Roll
Commercial warranty	-	10 year limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Surface treatment	-	Dura Tech®
Length	-	150 ft (46 m)
Type of product	-	Textile Flooring
Width	-	12 ft (3.66 m)