

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	ISO 1765	0.385 " (9.75 mm)
Installation method	-	Glue-Down
Format Type	-	Roll
Commercial warranty	-	10 year limited
Pile construction	-	Tip-sheared pile
Gauge	-	1/10"
Face Weight	-	46 oz/yd <sup>2</sup>
Pile density	ISO 8543	5571 oz/yd <sup>3</sup>
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	ISO 2424	Super-Lok®
Primary backing	-	Woven Polypropylene

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Electrostatic Propensity	-	$\leq 3.5$ kV
Colorfastness to Light	-	$\geq 4$ after 60 hours

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP0025
ReStart®	-	Yes
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Maximum pile height	-	0.2750 " (6.99 mm)
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Tip-sheared pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.385 " (9.75 mm)
Electrostatic Propensity	-	$\leq 3.5$ kV
Gauge	-	1/10"
Colorfastness to Light	AATCC 16E	$\geq 4$ after 60 hours

	Standard	Tarkett value
<b>Stitches/Rows per Inch</b>	-	10.20 /in
<b>Minimum pile height</b>	-	0.2570 " (6.53 mm)
<b>Pile density</b>	-	5571 oz/yd <sup>3</sup>
<b>Fiber System</b>	-	Antron® Legacy Nylon
<b>Dye Method</b>	-	Solution Dyed / Yarn Dyed
<b>Secondary backing</b>	-	Super-Lok®
<b>Primary backing</b>	-	Woven Polypropylene
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Suri 44043
<b>Pattern type</b>	-	Texture
<b>Pattern scale</b>	-	Small
<b>Pattern match</b>	-	No
<b>Pattern repeat width</b>	-	0.20 "
<b>Format Type</b>	-	Roll
<b>Commercial warranty</b>	-	10 year limited
<b>Flammability</b>	ASTM E648	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
<b>Smoke Density</b>	ASTM E662	< 450
<b>Surface treatment</b>	-	Dura Tech®
<b>Length</b>	-	150 ft (46 m)
<b>Type of product</b>	-	Textile Flooring
<b>Width</b>	-	12 ft (3.66 m)