

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.265 " (6.73 mm)
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Commercial warranty	-	10 year limited
Installation method	-	Glue-Down
Pattern	-	Tatami III 56071
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Texture
Format Type	-	Roll
Maximum pile height	-	0.2160 " (5.49 mm)
Pile construction	-	Textured loop pile
Gauge	-	1/10"
Stitches/Rows per Inch	-	12.70 /in
Minimum pile height	-	0.0790 " (2.01 mm)
Pile density	-	7315 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	0.47 "
Pattern repeat width	-	0.40 "
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	≥ 8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	AATCC 16E	≥ 4 after 100 hours
Length	-	150 ft (46 m)
Width	-	12 ft (3.66 m)
Face Weight	-	30 oz/yd ²

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP0025
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product