

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.305 " (7.75 mm)
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Commercial warranty	-	10 year limited
Installation method	-	Glue-Down
Pattern	-	Travertine 40009
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Organic
Format Type	-	Roll
Maximum pile height	-	0.2170 " (5.51 mm)
Pile construction	-	Patterned Tipshear
Gauge	-	5/64"
Stitches/Rows per Inch	-	13.20 /in
Minimum pile height	-	0.0790 " (2.01 mm)
Pile density	-	7555 oz/yd ³
Fiber System	-	XTI® Nylon
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Pattern scale	-	Large
Pattern match	-	Yes
Pattern repeat length	-	34.09 "
Pattern repeat width	-	18.75 "
Soil protection	-	Application Rate: 2% of Face Weight
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	AATCC 16E	≥ 4 after 60 hours
Length	-	105 ft (32 m)
Width	-	12.5 ft (3.81 m)
Face Weight	-	32 oz/yd ²

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP1828
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product



Travertine

Travertine 40009 BROWNSTONE 02299