

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.305 " (7.75 mm)
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Commercial warranty	-	20 year limited
Installation method	-	Glue-Down
Pattern	-	Woodrush 44059
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Organic
Format Type	-	Roll
Maximum pile height	-	0.2370 " (6.02 mm)
Pile construction	-	Patterned Tipshear
Gauge	-	1/10"
Stitches/Rows per Inch	-	13 /in
Minimum pile height	-	0.0790 " (2.01 mm)
Pile density	-	7326 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	LifeLONG®
Primary backing	-	Woven Polypropylene
Pattern scale	-	Large
Pattern match	-	Yes
Pattern repeat length	-	27.69 "
Pattern repeat width	-	24 "
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	≥ 8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Colorfastness to Light	AATCC 16E	≥ 4 after 100 hours
Length	-	150 ft (46 m)
Width	-	12 ft (3.66 m)
Face Weight	-	30 oz/yd ²

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	35 %
CRI Green Label Plus Certification	-	GLP6595

Standard

Tarkett value

Antimicrobial Chemicals

-

No antimicrobials (EPA Registered pesticides) added to product