

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.205 " (5.26 mm)
Flammability	ASTM E648	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Smoke Density	ASTM E662	< 450
Commercial warranty	-	10 year limited
Installation method	-	Glue-Down
Pattern	-	Yohji Grid II 30398
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Linear
Format Type	-	Roll
Maximum pile height	-	0.1570 " (3.99 mm)
Pile construction	-	Patterned loop pile
Gauge	-	1/10"
Stitches/Rows per Inch	-	13.80 /in
Minimum pile height	-	0.0980 " (2.49 mm)
Pile density	-	6099 oz/yd <sup>3</sup>
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Pattern scale	-	Large
Pattern match	-	Yes
Pattern repeat length	-	9.13 "
Pattern repeat width	-	6 "
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	$\geq 8$
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	$\leq 3.5$ kV
Colorfastness to Light	AATCC 16E	$\geq 4$ after 100 hours
Length	-	150 ft (46 m)
Width	-	12 ft (3.66 m)
Face Weight	-	22 oz/yd <sup>2</sup>

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %



Yohji Grid II

Yohji Grid II 30398 CHISEL 01344

	Standard	Tarkett value
--	----------	---------------

<b>CRI Green Label Plus Certification</b>	-	GLP0025
---	---	---------

<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product
--------------------------------	---	--