

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

|                      | Standard  | Tarkett value                             |
|----------------------|-----------|---|
| Construction Process | -         | TUFTED                                    |
| Total thickness      | ISO 24346 | 0.280 " (7.06 mm)                         |
| Installation method  | -         | Glue-Down                                 |
| Format Type          | -         | Tile                                      |
| Items per box        | -         | 15  |
| Surface per box      | -         | 6.67 sq. yd                               |
| Box per pallet       | -         | 30  |
| Commercial warranty  | -         | Lifetime Limited                          |
| Surface treatment    | -         | Eco-Ensure(Fluorine-Free Soil Protection) |
| Pile construction    | -         | Patterned loop pile                       |
| Gauge                | -         | 5/64"                                     |
| Pile thickness       | ISO 1766  | 0.105 " (2.62 mm)                         |
| Face Weight          | -         | 19 oz/yd <sup>2</sup>                     |
| Pile density         | ISO 8543  | 122880000000 g/m <sup>3</sup>             |
| Dye Method           | -         | Solution Dyed / Yarn Dyed                 |
| Secondary backing    | ISO 2424  | ethos® Modular with Omnicat Technology™   |
| Primary backing      | -         | Synthetic Non-Woven                       |

### TECHNICAL PERFORMANCE

|                          | Standard | Tarkett value                       |
|--------------------------|----------|-------------------------------------|
| Flammability             | -        | Class 1 (≥ 0.45 W/cm <sup>2</sup> ) |
| Electrostatic Propensity | -        | ≤ 3.0 kV                            |
| Colorfastness to Light   | -        | ≥ 4 after 60 hours                  |
| Is cutable               | -        | No                                  |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|                                    | Standard | Tarkett value  |
|------------------------------------|----------|--|
| Cradle-to-Cradle                   | -        | Silver   |
| CRI Green Label Plus Certification | -        | GLP8320  |
| ReStart®                           | -        | Yes  |
| DECLARE                            | -        | Yes  |
| Third Party Certification NSF-140  | -        | Platinum   |
| Antimicrobial Chemicals            | -        | No antimicrobials (EPA Registered pesticides) added to product |
| Pre Consumer recycled content      | -        | 25 %   |
| Post Consumer recycled content     | -        | 37 %   |

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                                 | Standard   | Tarkett value                              |
|---------------------------------|------------|--|
| <b>Construction</b>             | Standard   | Tarkett value<br>Stratatec® Patterned Loop |
| <b>Soil protection</b>          | -          | Application Rate: 2% of Face Weight        |
| <b>Pile construction</b>        | -          | Patterned loop pile                        |
| <b>Surface Flammability</b>     | -          | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70     |
| <b>Total thickness</b>          | ASTM F386  | 0.280 " (7.06 mm)                          |
| <b>Electrostatic Propensity</b> | -          | ≤ 3.0 kV                                   |
| <b>Gauge</b>                    | -          | 5/64"                                      |
| <b>Colorfastness to Light</b>   | AATCC 16E  | ≥ 4 after 60 hours                         |
| <b>Stitches/Rows per Inch</b>   | -          | 10 /in                                     |
| <b>Pile thickness</b>           | ASTM D5848 | 0.105 " (2.62 mm)                          |
| <b>Average pile height</b>      | -          | 0.185 " (5 mm)                             |
| <b>Pile density</b>             | -          | 122880000000 g/m <sup>3</sup>              |
| <b>Fiber System</b>             | -          | Dynex® Nylon                               |
| <b>Dye Method</b>               | -          | Solution Dyed / Yarn Dyed                  |
| <b>Secondary backing</b>        | -          | ethos® Modular with Omnicat Technology™    |
| <b>Primary backing</b>          | -          | Synthetic Non-Woven                        |
| <b>Installation method</b>      | -          | Glue-Down                                  |
| <b>Pattern</b>                  | -          | Accentuate 04255                           |
| <b>Pattern type</b>             | -          | Geometric                                  |
| <b>Pattern scale</b>            | -          | Medium                                     |
| <b>Pattern match</b>            | -          | No   |
| <b>Format Type</b>              | -          | Tile                                       |
| <b>Commercial warranty</b>      | -          | Lifetime Limited                           |
| <b>Flammability</b>             | ASTM E648  | Class 1 (≥ 0.45 W/cm <sup>2</sup> )        |
| <b>Smoke Density</b>            | ASTM E662  | 450 or Less                                |
| <b>Surface treatment</b>        | -          | Eco-Ensure(Fluorine-Free Soil Protection)  |
| <b>Type of product</b>          | -          | Textile Flooring                           |
| <b>Length</b>                   | -          | 24 " (610 mm)                              |
| <b>Width</b>                    | -          | 24 " (610 mm)                              |