

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Flammability	ASTM E648	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Smoke Density	ASTM E662	450 or Less
Commercial warranty	-	Lifetime Limited
Total thickness	ASTM F386	0.185 " (4.70 mm)
Installation method	-	Glue-Down
Pattern	-	All Star 02931
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Linear
Format Type	-	Tile
Construction	-	Textured Loop
Pile construction	-	Level loop pile
Gauge	-	1/13"
Stitches/Rows per Inch	-	7.20 /in
Pile thickness	ASTM D5848	0.090 " (2.26 mm)
Average pile height	-	0.115 " (3 mm)
Fiber System	-	Dynex SD® Nylon / Dynex® Nylon
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	ethos® Modular with Omnicat Technology™
Primary backing	-	Synthetic Non-Woven
Pattern scale	-	Medium
Soil protection	-	Application Rate: 2% of Face Weight
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	$\leq 3.0$ kV
Colorfastness to Light	AATCC 16E	$\geq 4$ after 60 hours
Face Weight	-	17 oz/yd <sup>2</sup>

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
ReStart®	-	Yes
DECLARE	-	Yes
Pre Consumer recycled content	-	24 %
Post Consumer recycled content	-	35 %
CRI Green Label Plus Certification	-	GLP8320
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product



All Star

All Star 02931 ATLANTIS 17306