

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|-----------------------------|----------|---|
| Construction Process | ISO 2424 | TUFTED |
| Installation method | - | Glue-Down |
| Format Type | - | Tile |
| Items per box | - | 15 |
| Surface per box | - | 6.667 sq. yd |
| Box per pallet | - | 30 |
| Commercial warranty | - | Lifetime Limited |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | ethos® Modular with Omniccoat Technology™ |
| Pile construction | - | Level loop pile |
| Gauge | - | 1/13" |
| Pile thickness | ISO 1766 | 0.090 " (2.26 mm) |
| Face Weight | - | 17 oz/yd ² |
| Pile density | ISO 8543 | 2488.32 oz/yd ³ |
| Dye Method | - | Solution Dyed / Yarn Dyed |
| Primary backing | - | Synthetic Non-Woven |
| Fiber System | ISO 2424 | Dynex® Nylon |
| Cradle-to-Cradle | - | Silver |
| DECLARE | - | Yes |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|---------------------------------|----------|---|
| Flammability | - | Class 1 (≥ 0.45 W/cm ²) |
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Colorfastness to Light | - | ≥ 4 after 60 hours |
| Is cutable | - | No |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method | - | Glue-Down |
| Format Type | - | Tile |
| Items per box | - | 15 |

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

| | Standard | Tarkett value |
|---|----------|---------------|
| Cradle-to-Cradle | - | Silver |
| CRI Green Label Plus Certification | - | GLP8320 |
| ReStart® | - | Yes |
| DECLARE | - | Yes |
| Third Party Certification NSF-140 | - | Platinum |

| | Standard | Tarkett value |
|-------------------------------------|----------|--|
| Antimicrobial Chemicals | - | No antimicrobials (EPA Registered pesticides) added to product |
| Recycled Content - Production Waste | - | 24 % |
| Post Consumer recycled content | - | 35 % |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------------|------------|---|
| Construction | - | Textured Loop |
| Soil protection | - | Application Rate: 2% of Face Weight |
| Pile construction | - | Level loop pile |
| Surface Flammability | - | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70 |
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Gauge | - | 1/13" |
| Colorfastness to Light | AATCC 16E | ≥ 4 after 60 hours |
| Stitches/Rows per Inch | - | 7.20 /in |
| Pile thickness | ASTM D5848 | 0.090 " (2.26 mm) |
| Average pile height | - | 0.115 " (3 mm) |
| Pile density | - | 2488.32 oz/yd ³ |
| Fiber System | - | Dynex® Nylon |
| Dye Method | - | Solution Dyed / Yarn Dyed |
| Secondary backing | - | ethos® Modular with Omnicoat Technology™ |
| Primary backing | - | Synthetic Non-Woven |
| Installation method | - | Glue-Down |
| Pattern | - | All Star 02931 |
| Pattern type | - | Linear |
| Pattern scale | - | Medium |
| Format Type | - | Tile |
| Commercial warranty | - | Lifetime Limited |
| Flammability | ASTM E648 | Class 1 (≥ 0.45 W/cm ²) |
| Smoke Density | ASTM E662 | 450 or Less |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Type of product | - | Textile Flooring |
| Length | - | 24 " |
| Width | - | 24 " |
| Items per box | - | 15 |