

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	ISO 24346	0.280 " (7.06 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Items per box	-	15
Surface per box	-	6.67 sq. yd
Box per pallet	-	30
Commercial warranty	-	Lifetime Limited
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Pile thickness	ISO 1766	0.100 " (2.59 mm)
Face Weight	-	21 oz/yd <sup>2</sup>
Pile density	ISO 8543	136960000000 g/m <sup>3</sup>
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	ISO 2424	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Electrostatic Propensity	-	$\leq 3.0$ kV
Colorfastness to Light	-	$\geq 4$ after 60 hours

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
CRI Green Label Plus Certification	-	GLP8320
ReStart®	-	Yes
DECLARE	-	Yes
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	23 %
Post Consumer recycled content	-	34 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value

	Standard	Tarkett value
<b>Construction</b>	-	Stratatec® Patterned Loop
<b>Soil protection</b>	-	Application Rate: 2% of Face Weight
<b>Pile construction</b>	-	Patterned loop pile
<b>Surface Flammability</b>	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
<b>Total thickness</b>	ASTM F386	0.280 " (7.06 mm)
<b>Electrostatic Propensity</b>	-	≤ 3.0 kV
<b>Gauge</b>	-	5/64"
<b>Colorfastness to Light</b>	AATCC 16E	≥ 4 after 60 hours
<b>Stitches/Rows per Inch</b>	-	10.80 /in
<b>Pile thickness</b>	ASTM D5848	0.100 " (2.59 mm)
<b>Average pile height</b>	-	0.185 " (5 mm)
<b>Pile density</b>	-	136960000000 g/m <sup>3</sup>
<b>Fiber System</b>	-	Dynex SD® Nylon / Dynex® Nylon
<b>Dye Method</b>	-	Solution Dyed / Yarn Dyed
<b>Secondary backing</b>	-	ethos® Modular with Omnicoat Technology™
<b>Primary backing</b>	-	Synthetic Non-Woven
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Angulate 04655
<b>Pattern type</b>	-	Geometric
<b>Pattern scale</b>	-	Large
<b>Pattern match</b>	-	Yes
<b>Pattern repeat length</b>	-	95.33 "
<b>Pattern repeat width</b>	-	72 "
<b>Format Type</b>	-	Tile
<b>Commercial warranty</b>	-	Lifetime Limited
<b>Flammability</b>	ASTM E648	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
<b>Smoke Density</b>	ASTM E662	450 or Less
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Type of product</b>	-	Textile Flooring
<b>Length</b>	-	24 " (610 mm)
<b>Width</b>	-	24 " (610 mm)