

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

|                             | Standard | Tarkett value                             |
|-----------------------------|----------|---|
| <b>Pile thickness</b>       | ISO 1766 | 0.085 " (2.21 mm)                         |
| <b>Fiber System</b>         | ISO 2424 | Dynex® Nylon                              |
| <b>Format Type</b>          | -        | Tile                                      |
| <b>Items per box</b>        | -        | 15  |
| <b>Construction Process</b> | ISO 2424 | TUFTED                                    |
| <b>Installation method</b>  | -        | Glue-Down                                 |
| <b>Surface per box</b>      | -        | 6.667 sq. yd                              |
| <b>Box per pallet</b>       | -        | 30  |
| <b>Commercial warranty</b>  | -        | Lifetime Limited                          |
| <b>Surface treatment</b>    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>    | ISO 2424 | ethos® Modular with Omnicoat Technology™  |
| <b>Pile construction</b>    | -        | Level loop pile                           |
| <b>Gauge</b>                | -        | 1/13"                                     |
| <b>Face Weight</b>          | -        | 18 oz/yd <sup>2</sup>                     |
| <b>Pile density</b>         | ISO 8543 | 2833.92 oz/yd <sup>3</sup>                |
| <b>Dye Method</b>           | -        | Solution dyed                             |
| <b>Primary backing</b>      | -        | Synthetic Non-Woven                       |
| <b>Cradle-to-Cradle</b>     | -        | Silver                                    |
| <b>DECLARE</b>              | -        | Yes                                       |

### TECHNICAL PERFORMANCE

|                                 | Standard | Tarkett value                             |
|---------------------------------|----------|---|
| <b>Flammability</b>             | -        | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Electrostatic Propensity</b> | -        | $\leq 3.0$ kV                             |
| <b>Colorfastness to Light</b>   | -        | $\geq 4$ after 60 hours                   |
| <b>Is cuttable</b>              | -        | No  |
| <b>Surface treatment</b>        | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>      | -        | Glue-Down                                 |
| <b>Format Type</b>              | -        | Tile                                      |
| <b>Items per box</b>            | -        | 15  |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|  | Standard | Tarkett value |
|--|----------|---------------|
| <b>Cradle-to-Cradle</b>                    | -        | Silver        |
| <b>ReStart®</b>                            | -        | Yes           |
| <b>CRI Green Label Plus Certification</b>  | -        | GLP8320       |
| <b>DECLARE</b>                             | -        | Yes           |
| <b>Recycled Content - Production Waste</b> | -        | 24 %          |

|  | Standard | Tarkett value  |
|--|----------|--|
| <b>Third Party Certification NSF-140</b> | -        | Platinum   |
| <b>Antimicrobial Chemicals</b>           | -        | No antimicrobials (EPA Registered pesticides) added to product |
| <b>Post Consumer recycled content</b>    | -        | 35 %   |

## CHARACTERISTICS & TECHNICAL PERFORMANCE

|                                 | Standard   | Tarkett value                             |
|---------------------------------|------------|---|
| <b>Type of product</b>          | -          | Textile Flooring                          |
| <b>Length</b>                   | -          | 24 "                                      |
| <b>Width</b>                    | -          | 24 "                                      |
| <b>Pattern</b>                  | -          | Applause III 02803                        |
| <b>Commercial warranty</b>      | -          | Lifetime Limited                          |
| <b>Flammability</b>             | ASTM E648  | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Smoke Density</b>            | ASTM E662  | 450 or Less                               |
| <b>Surface treatment</b>        | -          | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>      | -          | Glue-Down                                 |
| <b>Pattern type</b>             | -          | Texture                                   |
| <b>Format Type</b>              | -          | Tile                                      |
| <b>Construction</b>             | -          | Level Loop                                |
| <b>Soil protection</b>          | -          | Application Rate: 2% of Face Weight       |
| <b>Pile construction</b>        | -          | Level loop pile                           |
| <b>Surface Flammability</b>     | -          | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| <b>Electrostatic Propensity</b> | -          | $\leq 3.0$ kV                             |
| <b>Gauge</b>                    | -          | 1/13"                                     |
| <b>Colorfastness to Light</b>   | AATCC 16E  | $\geq 4$ after 60 hours                   |
| <b>Stitches/Rows per Inch</b>   | -          | 8.20 /in                                  |
| <b>Pile thickness</b>           | ASTM D5848 | 0.085 " (2.21 mm)                         |
| <b>Average pile height</b>      | -          | 0.115 " (3 mm)                            |
| <b>Pile density</b>             | -          | 2833.92 oz/yd <sup>3</sup>                |
| <b>Fiber System</b>             | -          | Dynex® Nylon                              |
| <b>Dye Method</b>               | -          | Solution dyed                             |
| <b>Secondary backing</b>        | -          | ethos® Modular with Omnicat Technology™   |
| <b>Primary backing</b>          | -          | Synthetic Non-Woven                       |
| <b>Pattern scale</b>            | -          | Medium                                    |
| <b>Items per box</b>            | -          | 15  |