

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	-	Stratatec® Patterned Loop
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned loop pile
Stain Resistance	AATCC 175-08	≥8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.280 " (7.06 mm)
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	5/64"
Stitches/Rows per Inch	-	9.60 /in
Pile thickness	ASTM D5848	0.080 " (2.06 mm)
Average pile height	-	0.185 " (5 mm)
Pile density	-	3317760 oz/yd ³
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Installation method	-	Glue-Down
Pattern	-	Change II 03747
Pattern type	-	Linear
Commercial warranty	-	Lifetime Limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	450 or Less

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
CRI Green Label Plus Certification	-	GLP8320
ReStart®	-	Yes
DECLARE	-	Yes
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Recycled Content - Production Waste	-	23 %
Post Consumer recycled content	-	34 %