

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450
Pattern	-	District 03500
Pattern type	-	Geometric
Pattern scale	-	Large
Pattern repeat length	-	123.670 "
Pattern repeat width	-	72 "
Format Type	-	Tile
Dye Method	-	Solution Dyed
Fiber System	-	Antron Lumena® Nylon
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	Modular ethos® with Omnicoat Technology™
Total thickness	ASTM F386	0.278 " (7.06 mm)
Face Weight	-	21 oz/yd ²
Installation method	-	Glue-Down

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP8320
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	29 %
Post Consumer recycled content	-	33.4 %
Third Party Certification NSF-140	-	Platinum