

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Professional warranty (in years)</b>	-	Lifetime Limited
<b>Pattern</b>	-	Echelon 04771
<b>Pattern type</b>	-	Linear
<b>Pattern scale</b>	-	Small
<b>Format Type</b>	-	Tile
<b>Dye Method</b>	-	Solution Dyed / Yarn Dyed
<b>Fiber System</b>	-	Dynex® Nylon
<b>Primary backing</b>	-	Synthetic Non-Woven
<b>Secondary backing</b>	-	Modular Flex Aire® Cushion, Modular ER3® RS, Modular ER3®, Modular ethos® with Omnicoat Technology™
<b>Total thickness</b>	ASTM F386	0.385 " (9.75 mm), 0.315 " (8 mm), 0.280 " (7.05 mm)
<b>Pile thickness</b>	ASTM D5848	0.085 " (2.20 mm)
<b>Face Weight</b>	-	28 oz/yd <sup>2</sup>
<b>Installation method</b>	-	Glue-Down, Peel & Stick
<b>Flooring Radiant Panel</b>	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
<b>Smoke Generation</b>	ASTM E662	< 450

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>ReStart®</b>	-	Yes
<b>CRI Green Label Plus Certification</b>	-	GLP6558, GLP1366, GLP8320
<b>Cradle-to-Cradle</b>	-	Silver
<b>Pre Consumer recycled content</b>	-	18 %, 34.20 %, 30.50 %, 29 %
<b>Post Consumer recycled content</b>	-	5 %, 15.5 %, 19.2 %, 31.2 %
<b>Third Party Certification NSF-140</b>	-	Gold, Platinum