

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Pattern	-	Element 04468
Pattern type	-	Linear
Format Type	-	Tile
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Total thickness	-	0.280 " (7.06 mm)
Installation method	-	Glue-Down
Flammability - Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Colorfastness to Light	AATCC 16E	> 4 after 100 hours
Smoke Generation	ASTM E662	< 450
Pattern scale	-	Medium
Construction	-	Stratatec® Patterned Loop
Dye Method	-	Solution Dyed / Yarn Dyed
Fiber System	-	Dynex® Nylon
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	Modular ethos® with Omnicoat Technology™
Type of product	-	Textile Flooring

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	29 %
Cradle-to-Cradle	-	Silver
CRI Green Label Plus Certification	-	GLP8320
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Post Consumer recycled content	-	35.2 %
Third Party Certification NSF-140	-	Platinum