

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Pattern</b>	-	Element 04468
<b>Pattern type</b>	-	Linear
<b>Format Type</b>	-	Tile
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Total thickness</b>	-	0.280 " (7.06 mm)
<b>Installation method</b>	-	Glue-Down
<b>Flammability - Flooring Radiant Panel</b>	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
<b>Colorfastness to Light</b>	AATCC 16E	> 4 after 100 hours
<b>Smoke Generation</b>	ASTM E662	< 450
<b>Pattern scale</b>	-	Medium
<b>Construction</b>	-	Stratatec® Patterned Loop
<b>Dye Method</b>	-	Solution Dyed / Yarn Dyed
<b>Fiber System</b>	-	Dynex® Nylon
<b>Primary backing</b>	-	Synthetic Non-Woven
<b>Secondary backing</b>	-	Modular ethos® with Omnicoat Technology™
<b>Type of product</b>	-	Textile Flooring

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>ReStart®</b>	-	Yes
<b>Pre Consumer recycled content</b>	-	29 %
<b>Cradle-to-Cradle</b>	-	Silver
<b>CRI Green Label Plus Certification</b>	-	GLP8320
<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product
<b>Post Consumer recycled content</b>	-	35.2 %
<b>Third Party Certification NSF-140</b>	-	Platinum