

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Professional warranty (in years)	-	Lifetime Limited
Pattern	-	Element 04468
Pattern type	-	Linear
Pattern scale	-	Medium
Format Type	-	Roll, Tile
Dye Method	-	Solution Dyed / Yarn Dyed
Fiber System	-	Dynex® Nylon
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	Please refer to the product page.
Total thickness	ASTM F386	0.385 " (9.75 mm), 0.315 " (7.95 mm), 0.315 " (8 mm), 0.280 " (7.05 mm)
Pile thickness	ASTM D5848	0.100 " (2.55 mm)
Face Weight	-	16 oz/yd ²
Installation method	-	Glue-Down, Peel & Stick
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP9744, GLP6558, GLP1366, GLP8320
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	0 %, 20 %, 37.40 %, 33.40 %, 29 %
Post Consumer recycled content	-	Please refer to the product page.
Third Party Certification NSF-140	-	Gold, Platinum