

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	EN 13329	0.230 " (5.79 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Items per box	-	15
Surface per box	-	6.67 sq. yd
Box per pallet	-	30
Commercial warranty	-	Lifetime Limited
Gauge	-	5/64"
Face Weight	-	20 oz/yd ²
Primary backing	-	Synthetic Non-Woven

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
CRI Green Label Plus Certification	-	GLP8320
ReStart®	-	Yes
DECLARE	-	Yes
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	23 %
Post Consumer recycled content	-	34 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	-	Stratatec® Patterned Syntex®
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.230 " (5.79 mm)
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	5/64"
Colorfastness to Light	AATCC 16E	≥ 4 after 60 hours
Stitches/Rows per Inch	-	9.90 /in
Pile thickness	ASTM D5848	0.115 " (2.90 mm)
Average pile height	-	0.185 " (5 mm)
Pile density	-	126700000000 g/m ³
Fiber System	-	Dynex® Nylon

	Standard	Tarkett value
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Installation method	-	Glue-Down
Pattern	-	Esparto 04119
Pattern type	-	Linear
Pattern scale	-	Small
Pattern match	-	No
Format Type	-	Tile
Commercial warranty	-	Lifetime Limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	450 or Less
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Length	-	24 " (610 mm)
Type of product	-	Textile Flooring
Width	-	24 " (610 mm)