

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450
Pattern	-	Link 04222, Lumen 04087
Pattern type	-	Geometric
Pattern scale	-	Large
Format Type	-	Tile
Dye Method	-	Solution Dyed, Solution Dyed / Yarn Dyed
Fiber System	-	Dynex SD® Nylon (Stain resist), Dynex® Nylon
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	Modular Flex Aire® Cushion, Modular ER3® RS, Modular ER3®, Modular ethos® with Omniccoat Technology™
Total thickness	ASTM F386	0.384 " (9.75 mm), 0.315 " (8 mm), 0.278 " (7.06 mm)
Pile thickness	ASTM D5848	0.103 " (2.62 mm), 0.122 " (3.10 mm)
Face Weight	-	12 oz/yd ² , 28 oz/yd ²
Installation method	-	Glue-Down, Peel & Stick
Professional warranty (in years)	-	Lifetime Limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP6558, GLP1366, GLP8320
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	21 %, 38.70 %, 34.50 %, 29 %, 21.40 %
Post Consumer recycled content	-	6 %, 17.5 %, 21.7 %, 36.8 %, 31.2 %
Third Party Certification NSF-140	-	Gold, Platinum