

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
Construction Process	ISO 2424	TUFTED
Total thickness	-	0.315 " (8 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Items per box	-	15
Surface per box	-	6.667 sq. yd
Box per pallet	-	30
Commercial warranty	-	Lifetime Limited
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omnicoat Technology™
Pile construction	-	Cut-and-loop pile
Gauge	-	1/10"
Pile thickness	ISO 1766	0.125 " (3.15 mm)
Face Weight	-	28 oz/yd <sup>2</sup>
Pile density	ISO 8543	3105000 oz/yd <sup>3</sup>
Dye Method	-	Solution Dyed / Yarn Dyed
Primary backing	-	Synthetic Non-Woven
Fiber System	ISO 2424	Dynex® Nylon

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Electrostatic Propensity	-	$\leq 3.0$ kV
Is cuttable	-	No

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
CRI Green Label Plus Certification	-	GLP8320
ReStart®	-	Yes
DECLARE	-	Yes
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Recycled Content - Production Waste	-	22 %
Post Consumer recycled content	-	31 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	Standard	Tarkett value Symtex®
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Cut-and-loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.315 " (8 mm)
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	1/10"
Stitches/Rows per Inch	-	11.50 /in
Pile thickness	ASTM D5848	0.125 " (3.15 mm)
Average pile height	-	0.255 " (7 mm)
Pile density	-	3105000 oz/yd <sup>3</sup>
Fiber System	-	Dynex® Nylon
Dye Method	-	Solution Dyed / Yarn Dyed
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Installation method	-	Glue-Down
Pattern	-	Response 04704
Pattern type	-	Geometric
Pattern scale	-	Medium
Pattern match	-	No
Format Type	-	Tile
Commercial warranty	-	Lifetime Limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
Smoke Density	ASTM E662	450 or Less
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Type of product	-	Textile Flooring
Length	-	24 "
Width	-	24 "
Items per box	-	15