

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Primary backing	-	Synthetic Non-Woven
Face Weight	-	14 oz/yd <sup>2</sup>

TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Pattern	-	Rock Solid II 04321
Pattern type	-	Allover
Pattern scale	-	Small
Format Type	-	Tile
Dye Method	-	Solution Dyed / Yarn Dyed
Fiber System	-	Dynex® Nylon
Secondary backing	-	Modular ethos® with Omniccoat Technology™
Total thickness	ASTM F386	0.185 " (4.70 mm)
Installation method	-	Glue-Down
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart® Ready	-	Yes
CRI Green Label Plus Certification	-	GLP8320
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	29 %
Post Consumer recycled content	-	36 %
Third Party Certification NSF-140	-	Platinum