

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	ISO 2424	TUFTED
Total thickness	-	0.280 " (7.06 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Items per box	-	15
Surface per box	-	6.667 sq. yd
Box per pallet	-	30
Commercial warranty	-	Lifetime Limited
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omnicat Technology™
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Pile thickness	ISO 1766	0.070 " (1.83 mm)
Face Weight	-	12 oz/yd ²
Pile density	ISO 8543	3456000 oz/yd ³
Dye Method	-	Solution dyed
Primary backing	-	Synthetic Non-Woven
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 (≥ 0.45 W/cm ²)
Electrostatic Propensity	-	≤ 3.0 kV
Is cuttable	-	No
Total thickness	-	0.280 " (7.06 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Items per box	-	15

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
CRI Green Label Plus Certification	-	GLP8320
ReStart®	-	Yes
DECLARE	-	Yes
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Recycled Content - Production Waste	-	25 %

Standard Tarkett value

Post Consumer recycled content - 37 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

Standard Tarkett value

Construction	-	Stratatec® Patterned Loop
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned loop pile
Stain Resistance	AATCC 175-08	≥8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.280 " (7.06 mm)
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	5/64"
Stitches/Rows per Inch	-	10 /in
Pile thickness	ASTM D5848	0.070 " (1.83 mm)
Average pile height	-	0.185 " (5 mm)
Pile density	-	3456000 oz/yd ³
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omniccoat Technology™
Primary backing	-	Synthetic Non-Woven
Installation method	-	Glue-Down
Pattern	-	Street Life 03973
Pattern type	-	Geometric
Pattern scale	-	Large
Pattern match	-	No
Pattern repeat length	-	41.40 "
Pattern repeat width	-	18.13 "
Format Type	-	Tile
Commercial warranty	-	Lifetime Limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	450 or Less
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Type of product	-	Textile Flooring
Length	-	24 "
Width	-	24 "
Items per box	-	15