

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450
Pattern	-	Willow 04607
Pattern type	-	Organic
Pattern scale	-	Large
Pattern repeat length	-	118.850 "
Pattern repeat width	-	72 "
Format Type	-	Roll, Tile
Dye Method	-	Solution Dyed
Fiber System	-	Dynex SD® Nylon (Stain resist)
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	Please refer to the product page.
Total thickness	ASTM F386	0.384 " (9.75 mm), 0.313 " (7.95 mm), 0.315 " (8 mm), 0.278 " (7.06 mm)
Pile thickness	ASTM D5848	0.117 " (2.97 mm)
Face Weight	-	21 oz/yd ²
Installation method	-	Glue-Down, Peel & Stick
Professional warranty (in years)	-	Lifetime Limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP9744, GLP6558, GLP1366, GLP8320
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	0 %, 19 %, 32.10 %, 29 %
Post Consumer recycled content	-	8 %, 8.10 %, 6 %, 20.2 %, 33.4 %
Third Party Certification NSF-140	-	Gold, Platinum