

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450
Pattern	-	Avant 04840
Pattern type	-	Organic
Pattern scale	-	Large
Pattern repeat length	-	94.230 "
Pattern repeat width	-	72 "
Format Type	-	Tile, Roll
Dye Method	-	Solution Dyed
Fiber System	-	Dynex SD® Nylon (Stain resist)
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	Please refer to the product page.
Total thickness	ASTM F386	0.284 " (7.21 mm), 0.197 " (5 mm), 0.353 " (8.97 mm), 0.282 " (7.16 mm)
Pile thickness	ASTM D5848	0.102 " (2.59 mm)
Face Weight	-	25 oz/yd ²
Installation method	-	Glue-Down, Peel & Stick
Professional warranty (in years)	-	Lifetime Limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP1366, GLP8320, GLP9744, GLP6558
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	Please refer to the product page.
Post Consumer recycled content	-	Please refer to the product page.
Third Party Certification NSF-140	-	Gold, Platinum