

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS
CHARACTERISTICS

	Standard	Tarkett value
Primary backing	-	Synthetic Non-Woven
Face Weight	-	27 oz/yd ²

TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Professional warranty (in years)	-	Lifetime Limited
Pattern	-	River's Edge 03936
Pattern type	-	Organic
Pattern scale	-	Large
Format Type	-	Roll
Dye Method	-	Solution Dyed
Secondary backing	-	Powerbond Medfloor®
Total thickness	ASTM F386	0.315 " (7.95 mm)
Pile thickness	ASTM D5848	0.090 " (2.30 mm)
Installation method	-	Glue-Down
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart® Ready	-	Yes
CRI Green Label Plus Certification	-	GLP9744
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	8 %
Third Party Certification NSF-140	-	Gold