

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|----------------------|----------|---|
| Construction Process | - | TUFTED |
| Installation method | - | Glue-Down |
| Format Type | - | Tile |
| Commercial warranty | - | Lifetime Limited |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Pile thickness | ISO 1766 | 0.095 " (2.46 mm) |
| Face Weight | - | 20 oz/yd ² |
| Dye Method | - | Solution Dyed |
| Secondary backing | ISO 2424 | ethos® Modular with Omnicat Technology™ |
| Primary backing | - | Synthetic Non-Woven |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------------|----------|---|
| Flammability | - | Class 1 (≥ 0.45 W/cm ²) |
| Electrostatic Propensity | - | ≤ 3.0 kV |

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

| | Standard | Tarkett value |
|------------------------------------|----------|--|
| Cradle-to-Cradle | - | Silver |
| CRI Green Label Plus Certification | - | GLP8320 |
| ReStart® | - | Yes |
| DECLARE | - | Yes |
| Third Party Certification NSF-140 | - | Platinum |
| Antimicrobial Chemicals | - | No antimicrobials (EPA Registered pesticides) added to product |
| Pre Consumer recycled content | - | 23 % |
| Post Consumer recycled content | - | 34 % |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------------|--------------|--|
| Construction | - | Stratatec® Patterned Syntex® |
| Soil protection | - | Application Rate: 2% of Face Weight |
| Pile construction | - | Patterned loop pile |
| Stain Resistance | AATCC 175-08 | ≥ 8 |
| Surface Flammability | - | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70 |
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Gauge | - | 5/64" |

| | Standard | Tarkett value |
|-------------------------------|------------|---|
| Stitches/Rows per Inch | - | 9.70 /in |
| Pile thickness | ASTM D5848 | 0.095 " (2.46 mm) |
| Average pile height | - | 0.185 " (5 mm) |
| Fiber System | - | Dynex SD® Nylon (Stain resist) |
| Dye Method | - | Solution Dyed |
| Secondary backing | - | ethos® Modular with Omnicat Technology™ |
| Primary backing | - | Synthetic Non-Woven |
| Installation method | - | Glue-Down |
| Pattern | - | Cartography 04843 |
| Pattern type | - | Organic |
| Pattern scale | - | Medium |
| Pattern repeat length | - | 105.15 " |
| Pattern repeat width | - | 72 " |
| Format Type | - | Tile |
| Commercial warranty | - | Lifetime Limited |
| Flammability | ASTM E648 | Class 1 (≥ 0.45 W/cm ²) |
| Smoke Density | ASTM E662 | 450 or Less |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Type of product | - | Textile Flooring |