

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	-	Stratatec® Patterned Syntex®
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Stitches/Rows per Inch	-	9.70 /in
Pile thickness	ASTM D5848	0.095 " (2.46 mm)
Average pile height	-	0.185 " (5 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution Dyed
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Installation method	-	Glue-Down
Pattern type	-	Organic
Pattern scale	-	Medium
Pattern repeat length	-	105.15 "
Pattern repeat width	-	72 "
Format Type	-	Tile
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	≥ 8
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	450 or Less
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.0 kV
Commercial warranty	-	Lifetime Limited

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
ReStart®	-	Yes
DECLARE	-	Yes
CRI Green Label Plus Certification	-	GLP8320
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	23 %
Post Consumer recycled content	-	34 %