

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
Construction Process	-	TUFTED
Total thickness	ISO 24346	0.195 " (5 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Commercial warranty	-	Lifetime Limited
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Pile thickness	ISO 1766	0.090 " (2.24 mm)
Face Weight	-	22 oz/yd <sup>2</sup>
Pile density	ISO 8543	102400000000 g/m <sup>3</sup>
Dye Method	-	Solution Dyed
Secondary backing	ISO 2424	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
Electrostatic Propensity	-	≤ 3.0 kV

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP8320
ReStart®	-	Yes
DECLARE	-	Yes
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Pre Consumer recycled content	-	23 %
Post Consumer recycled content	-	33 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	-	Stratatec® Patterned Loop
Soil protection	-	Application Rate: 2% of Face Weight
Pile construction	-	Patterned loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.195 " (5 mm)

	Standard	Tarkett value
<b>Electrostatic Propensity</b>	-	≤ 3.0 kV
<b>Gauge</b>	-	5/64"
<b>Stitches/Rows per Inch</b>	-	8 /in
<b>Pile thickness</b>	ASTM D5848	0.090 " (2.24 mm)
<b>Average pile height</b>	-	0.185 " (5 mm)
<b>Pile density</b>	-	102400000000 g/m³
<b>Fiber System</b>	-	TDX® Nylon
<b>Dye Method</b>	-	Solution Dyed
<b>Secondary backing</b>	-	ethos® Modular with Omnicat Technology™
<b>Primary backing</b>	-	Synthetic Non-Woven
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Marled Tweed 11072
<b>Pattern type</b>	-	Linear
<b>Pattern scale</b>	-	Large
<b>Pattern match</b>	-	No
<b>Format Type</b>	-	Tile
<b>Commercial warranty</b>	-	Lifetime Limited
<b>Flammability</b>	ASTM E648	Class 1 (≥ 0.45 W/cm²)
<b>Smoke Density</b>	ASTM E662	450 or Less
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Type of product</b>	-	Textile Flooring