

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Pile thickness	ISO 1766	0.140 " (3.51 mm)
Fiber System	ISO 2424	Dynex SD® Nylon
Format Type	-	Roll
Construction Process	ISO 2424	WOVEN
Installation method	-	Glue-Down
Commercial warranty	-	15 year limited
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	Crossweave Velvet
Face Weight	-	24 oz/yd ²
Pile density	ISO 8543	6270 oz/yd ³
Dye Method	-	Solution dyed

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 (≥ 0.45 W/cm ²)
Electrostatic Propensity	-	≤ 3.5 kV
Is cutable	-	Yes
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Format Type	-	Roll

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP100204
Recycled Content - Production Waste	-	0 %
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Post Consumer recycled content	-	0 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Length	-	1800 "
Width	-	144 "
Pattern	-	Halifax 66002
Commercial warranty	-	15 year limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)

	Standard	Tarkett value
Smoke Density	ASTM E662	< 450
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Texture
Format Type	-	Roll
Construction	-	Woven Velvet Textured Cut & Loop
Soil protection	-	Application Rate: 2% of Face Weight
Maximum pile height	-	0.1570 " (3.99 mm)
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Stitches/Rows per Inch	-	9 /in
Pile thickness	ASTM D5848	0.140 " (3.51 mm)
Average pile height	-	0.125 " (3 mm)
Minimum pile height	-	0.0970 " (2.46 mm)
Pile density	-	6270 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution dyed
Secondary backing	-	Crossweave Velvet
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	0.44 "
Pattern repeat width	-	0.25 "