

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Pattern</b>	-	Halifax 66002
<b>Pattern type</b>	-	Texture
<b>Format Type</b>	-	Roll
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Total thickness</b>	-	0.270 " (6.86 mm)
<b>Installation method</b>	-	Glue-Down
<b>Commercial warranty</b>	-	15 year limited
<b>Flammability - Flooring Radiant Panel</b>	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
<b>Surface Flammability</b>	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
<b>Electrostatic Propensity</b>	-	1.5 kV
<b>Colorfastness to Light</b>	AATCC 16E	> 4 after 100 hours
<b>Smoke Generation</b>	ASTM E662	< 450
<b>Pattern scale</b>	-	Small
<b>Pattern match</b>	-	Yes
<b>Pattern repeat length</b>	-	0.440 "
<b>Pattern repeat width</b>	-	0.250 "
<b>Construction</b>	-	Woven Velvet Textured Cut & Loop
<b>Dye Method</b>	-	Solution Dyed
<b>Fiber System</b>	-	Dynex SD® Nylon
<b>Secondary backing</b>	-	Crossweave Velvet
<b>Stitches/Rows per Inch</b>	-	9 /in
<b>Pile thickness</b>	ASTM D5848	0.140 " (3.51 mm)
<b>Average pile height</b>	-	0.125 " (3 mm)
<b>Type of product</b>	-	Textile Flooring

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>ReStart®</b>	-	Yes
<b>CRI Green Label Plus Certification</b>	-	GLP1828
<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product