

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### TECHNICAL PERFORMANCE & CHARACTERISTICS

|   | Standard  | Tarkett value  |
|---|-----------|--|
| <b>Professional warranty (in years)</b> | -         | 5 years limited                                      |
| <b>Pattern</b>                          | -         | INSPIRE  |
| <b>Pattern type</b>                     | -         | Texture  |
| <b>Laying direction</b>                 | -         | Same Direction                                       |
| <b>Format Type</b>                      | -         | Roll   |
| <b>ASTM Product type</b>                | -         | Sheet Vinyl Floor Covering with Backing (ASTM F1303) |
| <b>Surface treatment</b>                | -         | TopClean XP  |
| <b>Total thickness</b>                  | ASTM F386 | 0.080 " (2 mm)                                       |
| <b>Wear layer thickness</b>             | ASTM F410 | 31 mil (0.80 mm)                                     |
| <b>Installation method</b>              | -         | Glue-Down  |
| <b>Residual indentation ASTM F1914</b>  | -         | 1 mil (0.05 mm)                                      |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|                                      | Standard | Tarkett value  |
|--------------------------------------|----------|----------------|
| <b>ReStart® Ready</b>                | -        | Yes            |
| <b>Phthalate content</b>             | -        | Phthalate-free |
| <b>Floorscore certification</b>      | -        | Yes            |
| <b>Pre Consumer recycled content</b> | -        | 30 %           |
| <b>EPD available</b>                 | -        | Yes            |